

Product Description for SaxonCS-HE (Home Edition)



Version 13 released May 2026

Page 1/4

This document lists the features provided by SaxonCS 13 open source Home Edition (Saxon-HE), for .NET 8+.

This document does not form part of any contract unless expressly incorporated.

Language Support

1. XSLT (Transformation Processing)

1.1 XSLT 3.0 Basic Processor	Provides all mandatory features from the XSLT 3.0 specification (including try/catch, iterate, accumulators, maps, named modes, content value templates, and extended patterns, as well as features retained from XSLT 2.0).
1.2 XSLT 3.0 Serialization	Provides the serialization feature: specifically, the ability to convert the result trees produced as output of an XSLT transformation to lexical XML, or other formats including HTML, JSON, and plain text, under the control of serialization parameters defined in the stylesheet or via an external API.
1.3 XSLT 3.0 Compatibility	Provides XSLT 1.0 compatibility mode as defined in the XSLT 3.0 specification. If a stylesheet specifies <code>version="1.0"</code> , this causes certain constructs to behave in a way that retains the XSLT 1.0 behavior.
1.4 XSLT 3.0 Dynamic Evaluation	Provides use of the XSLT 3.0 instruction <code>xsl:evaluate</code> , which allows dynamic evaluation of XPath expressions.
1.5 XSLT 3.0 XPath 3.1 Feature	Provides full use of XPath 3.1 features, including XPath 3.1 functions, and maps and arrays. Note: Saxon supports XPath 3.1 unconditionally in XSLT 3.0 stylesheets, it does not offer a processing mode in which XPath is restricted to version 3.0.
1.6 XSLT 3.0 Higher-Order Functions	Provides higher-order functions: specifically, the ability to use functions as values, including dynamic function calls, inline functions, partial function application, and the standard higher-order functions defined in the XPath 3.1 function library.

Optional features not provided: XSLT 3.0 Schema Awareness, XSLT 3.0 Streaming, XSLT 4.0 Extensions.

For more details see: [XSLT 3.0 conformance](#).

Relevant W3C Specification: [XSLT 3.0 Recommendation \(08 June 2017\)](#).

2. XPath

2.1 XPath 3.1 Basic

Provides all XPath 3.1 features which do not require schema-awareness or higher-order functions. This includes an implementation of maps and arrays, and support for JSON, as well as language constructs retained from earlier XPath versions.

2.2 XPath 3.1 Higher-Order Functions

Provides higher-order functions: specifically, the ability to use functions as values, including dynamic function calls, inline functions, partial function application, and a library of built-in higher-order functions.

Optional features not provided: XPath 3.1 Schema Aware, XPath 4.0 Extensions.

For more details see: [XPath 3.1 conformance](#).

Relevant W3C Specification: [XPath 3.1 Recommendation \(21 March 2017\)](#).

3. XQuery

3.1 XQuery 3.1 Minimal Conformance

Provides Minimal Conformance (including try/catch and "group-by", as well as language features retained from earlier XQuery versions) as defined in section 5 of the XQuery 3.1 specification.

3.2 XQuery 3.1 Modules

Provides the Module feature, which allows a query to be made up of multiple modules.

3.3 XQuery 3.1 Serialization

Provides the Serialization feature. This allows the output of a query to be serialized as lexical XML, or in other formats including HTML, JSON, and plain text, under the control of serialization parameters contained either in the query itself, or supplied externally.

3.4 XQuery 3.1 Higher-Order Functions

Provides the Higher-Order Function feature. This provides the ability to use functions as values, including dynamic function calls, inline functions, partial function application, and a library of built-in higher-order functions.

Optional features not provided: XQuery 3.1 Schema Aware, XQuery 3.1 Typed Data, XQuery 3.1 Static Typing, XQuery Update 1.0, XQuery 4.0 Extensions.

For more details see: [XQuery 3.1 conformance](#).

Relevant W3C Specification: [XQuery 3.1 Recommendation \(21 March 2017\)](#).

Performance Features

4. Import stylesheet packages

Allows the importing of stylesheet packages in compiled form. Possible with all editions provided the package only uses features available in that edition. Note that this edition does not provide the ability to create compiled stylesheet packages.

For more details see: [Compiling a stylesheet](#).

5. Optimizer (Basic)

The Basic optimizer provided with all Saxon editions provides a wide range of static and dynamic optimizations including full pipelining of list operations, lazy evaluation of variables, elimination of redundant sorting operations, etc.

6. Reading W3C schemas and DTDs

The W3C web server routinely rejects requests for commonly-referenced files such as the DTD for XHTML, causing parsing failures. In response to this, Saxon now includes copies of these documents within the issued JAR/DLL file, and recognizes requests for these documents, satisfying the request using the local copy.

Extensibility

7. Extensibility using custom classes

Ability to write extension functions (for use in XSLT, XQuery, or XPath) by implementing a Saxon-defined interface and registering the implementation with the Saxon Configuration.

For more details see: [Extensibility](#).

Localization

8. Formatting numbers in English

Numbers can be formatted as words in English.

For more details see: [Formatting numbers](#).

9. Formatting dates in English

Product Description for SaxonCS-HE (Home Edition)



Version 13 released May 2026

Page 4/4

Dates can be formatted as words in English.

For more details see: [Formatting dates](#).

10. Sorting and collations using platform locales

Support for sorting and comparison of strings using the Unicode Collation Algorithm uses the collation facilities available directly from the core .NET library.

For more details see: [Sorting and collations](#).

Interfaces and APIs

11. .NET API

SaxonCS's interface for processing XSLT, XQuery, and XPath, on .NET.

For more details see: [Saxon API for .NET](#).

12. Support for DOM

Ability to use a DOM (Document Object Model) for the input and output of transformations and queries. On the .NET platform this includes the System.Xml DOM classes.

For more details see: [Object models](#).